

PAT-NO: JP401252037A  
DOCUMENT-IDENTIFIER: JP 01252037 A  
TITLE: TRANSMITTING ERROR CORRECTING SYSTEM  
PUBN-DATE: October 6, 1989

INVENTOR-INFORMATION:  
NAME  
YAMAGISHI, TAKASHI

ASSIGNEE-INFORMATION:  
NAME COUNTRY  
TOSHIBA CORP N/A

APPL-NO: JP63078876  
APPL-DATE: March 31, 1988

INT-CL (IPC): H04L001/16

US-CL-CURRENT: 714/746

ABSTRACT:

PURPOSE: To obtain all correct data for a short time even when the line quality of a transmitting line is lowered by storing plural transmitting frames, in which error data are included, and specifying the correct data in each data by majority.

CONSTITUTION: When it is detected that the error data are included in the transmitting frame to be transmitted from a transmitting side device, an abnormal responding signal is transmitted to the transmitting side device and the retransmission of the same transmitting frame is requested. Simultaneously, the transmitting frame to include the data is stored in one receiving buffer. Thus, each time the transmitting frame, in which

the error  
data exist, is received, the transmitting frame is successively  
stored to the  
receiving buffer. Next, the respective data in the same position to  
be stored  
in the respective receiving buffers are taken out and compared. The  
most data  
are obtained as the correct data at the position. When the correct  
data are  
replaced with the inputted error data of the transmitting frame, the  
correct  
data can be obtained in a receiving side. Thus, when the  
transmitting frame is  
received in three times in the most satisfactory condition with such  
a  
procedure, the error data can be corrected to the correct data.

COPYRIGHT: (C)1989,JPO&Japio